



## HD-85 MID MOUNT PLATFORM

Designed for traditional truck company operations, the Ferrara HD-85 Mid Mount Platform boasts over 300 cubic feet of usable compartment space and the ability to carry up to 200' of ground ladders. Couple this with an impressive 1000 pound tip load while flowing water while reaching a 5th floor building and overcoming a set-back of over 70 feet, and you'll want to learn more about the HD-85.

### SPECIFICATIONS

Chassis:	Inferno up to 600hp, Ultra up to 500hp
Body:	Extruded Aluminum - quint or truck (no pump/tank)
Compartments:	Left and right side full height, 25-26" deep lower/transverse over torque box
Ladder Storage:	Up to 200' ground ladders enclosed in full length torque box
Pump Size:	Up to 2250 gpm midship or 5000 gpm rear mount industrial
Tank Size:	Up to 300 gallons
Ladder and Reach:	5-section heavy duty rear mount aerial with -12° to +72° operational envelope -12° operation off left and right sides of truck 87' vertical reach at 72° and 86' horizontal reach at 0° 51' vertical & 74' horizontal reach at 30°
Rated Load Capacity:	1000 pounds dry / 500 pounds flowing 1500 gpm OR 1000# flowing 1000 gpm Up to 4500 pounds distributed + rated load in the platform while flowing capacity No restrictions on aerial or monitor movement or placement while flowing capacity
Platform:	20 square feet interior working area Dual, outward opening, bi-fold gates with 23.5" clear opening
Warranty:	10 year cab and body structural, 25 year aerial structural, 10 year waterway and waterway seals, 15 year torque box & stabilizer





## FEATURES & OPTIONS



Twin monitors are available both manual, 1 manual and 1 electric or both electric



Bi-fold opening gates provide up to a 24" wide opening, wide enough to accommodate a stair chair



Platform controls are located front-center, giving the operator the best view when positioning the bucket



Forward stabilizers are directly behind the cab and support the weight of the cab and chassis



Our NFPA mandated continuous handrails maintain constant contact between the ladder and platform



Operate at negative elevations up to -12° reaching over 11' below street level



Ferrara's optional rope rescue/lifting arm also doubles as a temporary stokes mount



Our optional parapet roof ladder bracket allows you to safely access a parapet roof from our platform



Well-lit ladder rungs for safe and easy night operations

